



Safety Data Sheet acc. to OSHA HCS

Page 1/9

Printing date 09/04/2024

Revision 3

Reviewed on 09/04/2024

1 Identification

- **Product identifier**
- **Trade name:** *EB-155TC (PART A)*
- **Product number:** BT 301 (A)
- **Application of the substance / the mixture** Epoxy Resin Adhesive
- **Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**
EPOXYSET INC.
718 Park East Drive
Woonsocket, RI 02895, USA
Phone: (401) 726-4500
www.epoxyset.com
- **Information department:** Product safety department: msds@epoxyset.com
- **Emergency telephone number:**
Chemtel (US transportation) 1-800-255-3924
International (call collect) +01-813-248-0585

2 Hazard(s) identification

- **Classification of the substance or mixture**



GHS07

Skin Irritation 2 H315 Causes skin irritation.
 Eye Irritation 2A H319 Causes serious eye irritation.
 Sensitization - Skin 1 H317 May cause an allergic skin reaction.

- **Label elements**
- **GHS label elements** The product is classified and labeled according to the Globally Harmonized System (GHS).
- **Hazard pictograms**



GHS07

- **Signal word** Warning
- **Hazard-determining components of labeling:**
reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight ≤ 700)
- **Hazard statements**
H315 Causes skin irritation.
H319 Causes serious eye irritation.
H317 May cause an allergic skin reaction.
- **Precautionary statements**
P261 Avoid breathing dust/fume/gas/mist/vapors/spray
P264 Wash thoroughly after handling.
P272 Contaminated work clothing must not be allowed out of the workplace.

(Contd. on page 2)

US

Safety Data Sheet

acc. to OSHA HCS

Printing date 09/04/2024

Revision 3

Reviewed on 09/04/2024

Trade name: **EB-155TC (PART A)**

(Contd. of page 1)

- P280 Wear protective gloves / eye protection / face protection.
 P302+P352 If on skin: Wash with plenty of water.
 P305+P351+P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
 P362+P364 Take off contaminated clothing and wash it before reuse.
 P333+P313 If skin irritation or rash occurs: Get medical advice/attention.
 P321 Specific treatment (see on this label).
 P337+P313 If eye irritation persists: Get medical advice/attention.
 P363 Wash contaminated clothing before reuse.
 P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

· **Classification system:**· **NFPA ratings (scale 0 - 4)**· **HMIS-ratings (scale 0 - 4)**

HEALTH	2	Health = 2
FIRE	1	Fire = 1
REACTIVITY	0	Reactivity = 0

· **Other hazards**· **Results of PBT and vPvB assessment**· **PBT:** Not applicable.· **vPvB:** Not applicable.

3 Composition/information on ingredients

· **Chemical characterization: Mixtures**· **Description:** Mixture of the substances listed below with nonhazardous additions.· **Dangerous components:**

21645-51-2	aluminium oxide (hydrated) in wetted form (non-particulate)	30-50%
25068-38-6	reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight ≤ 700)	30-50%
	Substituted Silane - Proprietary	≤2.5%

4 First-aid measures

· **Description of first aid measures**· **After inhalation:**

Supply fresh air and to be sure call for a doctor.

In case of unconsciousness place patient stably in side position for transportation.

· **After skin contact:** Immediately wash with water and soap and rinse thoroughly.· **After eye contact:** Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.· **After swallowing:** If symptoms persist consult doctor.· **Information for doctor:**· **Most important symptoms and effects, both acute and delayed** No further relevant information available.

(Contd. on page 3)

US

Safety Data Sheet

acc. to OSHA HCS

Printing date 09/04/2024

Revision 3

Reviewed on 09/04/2024

Trade name: **EB-155TC (PART A)**

(Contd. of page 2)

- **Indication of any immediate medical attention and special treatment needed**
No further relevant information available.

5 Fire-fighting measures

- **Extinguishing media**
- **Suitable extinguishing agents:** Use fire fighting measures that suit the environment.
- **Special hazards arising from the substance or mixture** No further relevant information available.
- **Advice for firefighters**
- **Protective equipment:** No special measures required.

6 Accidental release measures

- **Personal precautions, protective equipment and emergency procedures** Not required.
- **Environmental precautions:**
Inform respective authorities in case of seepage into water course or sewage system.
Do not allow to enter sewers/ surface or ground water.
- **Methods and material for containment and cleaning up:** Pick up mechanically.
- **Reference to other sections**
See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.
- **Protective Action Criteria for Chemicals**

· PAC-1:

21645-51-2	aluminium oxide (hydrated) in wetted form (non-particulate)	8.7 mg/m ³
25068-38-6	reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight ≤ 700)	90 mg/m ³
	Substituted Silane - Proprietary	9.3 mg/m ³
112945-52-5	Amorphous, fumed silica	18 mg/m ³
1333-86-4	Carbon black	9 mg/m ³

· PAC-2:

21645-51-2	aluminium oxide (hydrated) in wetted form (non-particulate)	73 mg/m ³
25068-38-6	reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight ≤ 700)	990 mg/m ³
	Substituted Silane - Proprietary	100 mg/m ³
112945-52-5	Amorphous, fumed silica	100 mg/m ³
1333-86-4	Carbon black	290 mg/m ³

· PAC-3:

21645-51-2	aluminium oxide (hydrated) in wetted form (non-particulate)	440 mg/m ³
25068-38-6	reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight ≤ 700)	5,900 mg/m ³
	Substituted Silane - Proprietary	230 mg/m ³
112945-52-5	Amorphous, fumed silica	630 mg/m ³
1333-86-4	Carbon black	1750 mg/m ³

 US
(Contd. on page 4)

Safety Data Sheet

acc. to OSHA HCS

Printing date 09/04/2024

Revision 3

Reviewed on 09/04/2024

Trade name: *EB-155TC (PART A)*

(Contd. of page 3)

7 Handling and storage

- **Handling:**
- **Precautions for safe handling** No special precautions are necessary if used correctly.
- **Information about protection against explosions and fires:** No special measures required.
- **Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:** Store at temperatures not exceeding 10°C. Keep cool.
- **Information about storage in one common storage facility:** Not required.
- **Further information about storage conditions:** Keep receptacle tightly sealed.
- **Specific end use(s)** No further relevant information available.

8 Exposure controls/personal protection

- **Additional information about design of technical systems:** No further data; see section 7.
- **Control parameters**
- **Components with limit values that require monitoring at the workplace:**
The following constituent is the only constituent of the product which has a PEL, TLV or other recommended exposure limit.
At this time, the other constituents have no known exposure limits.

21645-51-2 aluminium oxide (hydrated) in wetted form (non-particulate)

REL	Long-term value: 2 mg/m ³ as Al
-----	---

- **Additional information:** The lists that were valid during the creation were used as basis.
- **Exposure controls**
- **Personal protective equipment:**
- **General protective and hygienic measures:**
Keep away from foodstuffs, beverages and feed.
Immediately remove all soiled and contaminated clothing.
Wash hands before breaks and at the end of work.
Avoid contact with the eyes and skin.
- **Breathing equipment:** Not required.
- **Protection of hands:**



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

- **Material of gloves**
The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.
- **Penetration time of glove material**
The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

(Contd. on page 5)

US

Safety Data Sheet

acc. to OSHA HCS

Printing date 09/04/2024

Revision 3

Reviewed on 09/04/2024

Trade name: *EB-155TC (PART A)*

(Contd. of page 4)

· Eye protection:



Tightly sealed goggles

9 Physical and chemical properties

· Information on basic physical and chemical properties

· General Information

· Appearance:

Form: Liquid

Color: Black

· Odor: Characteristic

· Odor threshold: Not determined.

· pH-value: Not applicable.

· Change in condition

Melting point/Melting range: Undetermined.

Boiling point/Boiling range: Undetermined.

· Flash point: 200 °C (392 °F)

· Flammability (solid, gaseous): Not determined.

· Decomposition temperature: Not determined.

· Ignition temperature: Product is not selfigniting.

· Danger of explosion: Product does not present an explosion hazard.

· Explosion limits:

Lower: Not determined.

Upper: Not determined.

· Vapor pressure: Not applicable.

· Density at 20 °C (68 °F): 1.0235-1.0239 g/cm³ (8.54111-8.54445 lbs/gal)

· Relative density: Not determined.

· Vapor density: Not applicable.

· Evaporation rate: Not applicable.

· Solubility in / Miscibility with

Water: Soluble.

· Partition coefficient (n-octanol/water): Not determined.

· Viscosity:

Dynamic: Not applicable.

Kinematic: Not applicable.

· Solvent content:

VOC content: 0.00 %

Solids content: 100.0 %

(Contd. on page 6)

US

Safety Data Sheet

acc. to OSHA HCS

Printing date 09/04/2024

Revision 3

Reviewed on 09/04/2024

Trade name: **EB-155TC (PART A)**

(Contd. of page 5)

· **Other information**

No further relevant information available.

10 Stability and reactivity

- **Reactivity** No further relevant information available.
- **Chemical stability**
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **Possibility of hazardous reactions** No dangerous reactions known.
- **Conditions to avoid** No further relevant information available.
- **Incompatible materials:** No further relevant information available.
- **Hazardous decomposition products:** No dangerous decomposition products known.

11 Toxicological information

- **Information on toxicological effects**
- **Acute toxicity:**
- **Primary irritant effect:**
- **on the skin:** Irritant to skin and mucous membranes.
- **on the eye:** Irritating effect.
- **Sensitization:** Sensitization possible through skin contact.
- **Additional toxicological information:**
The product shows the following dangers according to internally approved calculation methods for preparations:
Irritant
- **Carcinogenic categories**

· **IARC (International Agency for Research on Cancer)**

1333-86-4 Carbon black

2B

· **NTP (National Toxicology Program)**

None of the ingredients is listed.

· **OSHA-Ca (Occupational Safety & Health Administration)**

None of the ingredients is listed.

12 Ecological information

- **Toxicity**
- **Aquatic toxicity:** No further relevant information available.
- **Persistence and degradability** No further relevant information available.
- **Behavior in environmental systems:**
- **Bioaccumulative potential** No further relevant information available.
- **Mobility in soil** No further relevant information available.
- **Ecotoxic effects:**
- **Remark:** Toxic for fish
- **Additional ecological information:**
- **General notes:**
Water hazard class 2 (Self-assessment): hazardous for water
Do not allow product to reach ground water, water course or sewage system.
Danger to drinking water if even small quantities leak into the ground.
Also poisonous for fish and plankton in water bodies.

(Contd. on page 7)

-US-

Safety Data Sheet

acc. to OSHA HCS

Printing date 09/04/2024

Revision 3

Reviewed on 09/04/2024

Trade name: **EB-155TC (PART A)**

(Contd. of page 6)

- Toxic for aquatic organisms
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **Other adverse effects** No further relevant information available.

13 Disposal considerations

- **Waste treatment methods**
- **Recommendation:**
Must not be disposed of together with household garbage. Do not allow product to reach sewage system.
- **Uncleaned packagings:**
- **Recommendation:** Disposal must be made according to official regulations.
- **Recommended cleansing agent:** Water, if necessary with cleansing agents.

14 Transport information

- | | |
|--|-----------------|
| · UN-Number | |
| · DOT, IMDG, IATA | not regulated |
| · UN proper shipping name | |
| · DOT, IMDG, IATA | not regulated |
| · Transport hazard class(es) | |
| · DOT, ADN, IMDG, IATA | |
| · Class | not regulated |
| · Packing group | |
| · DOT, IMDG, IATA | not regulated |
| · Environmental hazards: | Not applicable. |
| · Special precautions for user | Not applicable. |
| · Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code | Not applicable. |
| · UN "Model Regulation": | not regulated |

15 Regulatory information

- **Safety, health and environmental regulations/legislation specific for the substance or mixture**
No further relevant information available.
- **Sara**

· **Section 355 (extremely hazardous substances):**

None of the ingredients is listed.

· **Section 313 (Specific toxic chemical listings):**

None of the ingredients is listed.

· **TSCA (Toxic Substances Control Act):**

21645-51-2 aluminium oxide (hydrated) in wetted form (non-particulate)

ACTIVE

(Contd. on page 8)

US

Safety Data Sheet

acc. to OSHA HCS

Printing date 09/04/2024

Revision 3

Reviewed on 09/04/2024

Trade name: **EB-155TC (PART A)**

(Contd. of page 7)

25068-38-6	reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight ≤ 700)	ACTIVE
	Substituted Silane - Proprietary	ACTIVE
1333-86-4	Carbon black	ACTIVE

· **Hazardous Air Pollutants**

None of the ingredients is listed.

· **Proposition 65**· **Chemicals known to cause cancer:**

1333-86-4 Carbon black

· **Chemicals known to cause reproductive toxicity for females:**

None of the ingredients is listed.

· **Chemicals known to cause reproductive toxicity for males:**

None of the ingredients is listed.

· **Chemicals known to cause developmental toxicity:**

None of the ingredients is listed.

· **Carcinogenic categories**· **EPA (Environmental Protection Agency)**

None of the ingredients is listed.

· **TLV (Threshold Limit Value)**

1333-86-4 Carbon black

A4

· **NIOSH-Ca (National Institute for Occupational Safety and Health)**

1333-86-4 Carbon black

· **GHS label elements** The product is classified and labeled according to the Globally Harmonized System (GHS).· **Hazard pictograms**

GHS07

· **Signal word** Warning· **Hazard-determining components of labeling:**reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight ≤ 700)· **Hazard statements**

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H317 May cause an allergic skin reaction.

· **Precautionary statements**

P261 Avoid breathing dust/fume/gas/mist/vapors/spray

P264 Wash thoroughly after handling.

P272 Contaminated work clothing must not be allowed out of the workplace.

P280 Wear protective gloves / eye protection / face protection.

P302+P352 If on skin: Wash with plenty of water.

P305+P351+P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P362+P364 Take off contaminated clothing and wash it before reuse.

P333+P313 If skin irritation or rash occurs: Get medical advice/attention.

(Contd. on page 9)

-US

Safety Data Sheet

acc. to OSHA HCS

Printing date 09/04/2024

Revision 3

Reviewed on 09/04/2024

Trade name: **EB-155TC (PART A)**

(Contd. of page 8)

- P321 Specific treatment (see on this label).
 P337+P313 If eye irritation persists: Get medical advice/attention.
 P363 Wash contaminated clothing before reuse.
 P501 Dispose of contents/container in accordance with local/regional/national/international regulations.
- **Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· **Department issuing SDS:** Environment protection department.

· **Contact:** EHS Personnel

· **Date of preparation / last revision** 09/04/2024 / 2

· **Abbreviations and acronyms:**

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA)

HMIS: Hazardous Materials Identification System (USA)

VOC: Volatile Organic Compounds (USA, EU)

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

NIOSH: National Institute for Occupational Safety

OSHA: Occupational Safety & Health

TLV: Threshold Limit Value

PEL: Permissible Exposure Limit

REL: Recommended Exposure Limit

Skin Irritation 2: Skin corrosion/irritation – Category 2

Eye Irritation 2A: Serious eye damage/eye irritation – Category 2A

Sensitization - Skin 1: Skin sensitisation – Category 1

· *** Data compared to the previous version altered.**

US



Safety Data Sheet acc. to OSHA HCS

Page 1/11

Printing date 09/04/2024

Revision 2

Reviewed on 09/04/2024

1 Identification

- **Product identifier**
- **Trade name:** *EB-155TC (PART B)*
- **Product number:** BT-301 (B)
- **Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**
EPOXYSET INC.
718 Park East Drive
Woonsocket, RI 02895, USA
Phone: (401) 726-4500
www.epoxyset.com
- **Information department:** Product safety department: msds@epoxyset.com
- **Emergency telephone number:**
Chemtel (US transportation) 1-800-255-3924
International (call collect) +01-813-248-0585

2 Hazard(s) identification

- **Classification of the substance or mixture**



GHS08 Health hazard

Carcinogenicity 2 H351 Suspected of causing cancer. Route of exposure: Inhalation.
Toxic to Reproduction 2 H361 Suspected of damaging fertility or the unborn child.



GHS05 Corrosion

Skin Corrosion 1B H314 Causes severe skin burns and eye damage.
Eye Damage 1 H318 Causes serious eye damage.



GHS07

Acute Toxicity - Oral 4 H302 Harmful if swallowed.
Sensitization - Skin 1 H317 May cause an allergic skin reaction.

- **Label elements**
- **GHS label elements** The product is classified and labeled according to the Globally Harmonized System (GHS).
- **Hazard pictograms**



GHS05



GHS07



GHS08

(Contd. on page 2)

US

Safety Data Sheet

acc. to OSHA HCS

Printing date 09/04/2024

Revision 2

Reviewed on 09/04/2024

Trade name: **EB-155TC (PART B)**

(Contd. of page 1)

· **Signal word** Danger· **Hazard-determining components of labeling:**

nonylphenols
2-piperazin-1-ylethylamine
titanium dioxide

· **Hazard statements**

H302 Harmful if swallowed.
H314 Causes severe skin burns and eye damage.
H317 May cause an allergic skin reaction.
H351 Suspected of causing cancer. Route of exposure: Inhalation.
H361 Suspected of damaging fertility or the unborn child.

· **Precautionary statements**

P201 Obtain special instructions before use.
P202 Do not handle until all safety precautions have been read and understood.
P260 Do not breathe dusts or mists.
P264 Wash thoroughly after handling.
P270 Do not eat, drink or smoke when using this product.
P272 Contaminated work clothing must not be allowed out of the workplace.
P280 Wear protective gloves/protective clothing/eye protection/face protection.
P301+P312 If swallowed: Call a poison center/doctor if you feel unwell.
P301+P330+P331 If swallowed: Rinse mouth. Do NOT induce vomiting.
P303+P361+P353 If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P305+P351+P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P310 Immediately call a poison center/doctor.
P308+P313 IF exposed or concerned: Get medical advice/attention.
P321 Specific treatment (see on this label).
P333+P313 If skin irritation or rash occurs: Get medical advice/attention.
P363 Wash contaminated clothing before reuse.
P405 Store locked up.
P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

· **Classification system:**· **NFPA ratings (scale 0 - 4)**

Health = 3
Fire = 1
Reactivity = 0

· **HMIS-ratings (scale 0 - 4)**

Health = *3
Fire = 1
Reactivity = 0

· **Other hazards**· **Results of PBT and vPvB assessment**

· **PBT:** Not applicable.
· **vPvB:** Not applicable.

US

(Contd. on page 3)

Safety Data Sheet

acc. to OSHA HCS

Printing date 09/04/2024

Revision 2

Reviewed on 09/04/2024

Trade name: **EB-155TC (PART B)**

(Contd. of page 2)

3 Composition/information on ingredients

- **Chemical characterization: Mixtures**
- **Description:** Mixture of the substances listed below with nonhazardous additions.

- **Dangerous components:**

21645-51-2	aluminium oxide (hydrated) in wetted form (non-particulate)	30-50%
84852-15-3	nonylphenols	30-50%
140-31-8	2-piperazin-1-ylethylamine	11.500%
13463-67-7	titanium dioxide	≤2.5%
112945-52-5	Amorphous, fumed silica	≤2.5%

4 First-aid measures

- **Description of first aid measures**
- **General information:**
Immediately remove any clothing soiled by the product.
Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.
- **After inhalation:**
Supply fresh air and to be sure call for a doctor.
In case of unconsciousness place patient stably in side position for transportation.
- **After skin contact:** Immediately wash with water and soap and rinse thoroughly.
- **After eye contact:** Rinse opened eye for several minutes under running water. Then consult a doctor.
- **After swallowing:**
Immediately call a doctor.
Drink copious amounts of water and provide fresh air. Immediately call a doctor.
- **Information for doctor:**
- **Most important symptoms and effects, both acute and delayed** No further relevant information available.
- **Indication of any immediate medical attention and special treatment needed**
No further relevant information available.

5 Fire-fighting measures

- **Extinguishing media**
- **Suitable extinguishing agents:** Use fire fighting measures that suit the environment.
- **Special hazards arising from the substance or mixture** No further relevant information available.
- **Advice for firefighters**
- **Protective equipment:** No special measures required.

6 Accidental release measures

- **Personal precautions, protective equipment and emergency procedures**
Wear protective equipment. Keep unprotected persons away.
- **Environmental precautions:**
Inform respective authorities in case of seepage into water course or sewage system.
Do not allow to enter sewers/ surface or ground water.
- **Methods and material for containment and cleaning up:**
Use neutralizing agent.
Dispose contaminated material as waste according to section 13.

(Contd. on page 4)

Safety Data Sheet

acc. to OSHA HCS

Printing date 09/04/2024

Revision 2

Reviewed on 09/04/2024

Trade name: **EB-155TC (PART B)**

(Contd. of page 3)

Ensure adequate ventilation.

· **Reference to other sections**

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

· **Protective Action Criteria for Chemicals**· **PAC-1:**

21645-51-2	aluminium oxide (hydrated) in wetted form (non-particulate)	8.7 mg/m ³
84852-15-3	nonylphenols	3.9 mg/m ³
140-31-8	2-piperazin-1-ylethylamine	6.4 mg/m ³
13463-67-7	titanium dioxide	30 mg/m ³
112945-52-5	Amorphous, fumed silica	18 mg/m ³

· **PAC-2:**

21645-51-2	aluminium oxide (hydrated) in wetted form (non-particulate)	73 mg/m ³
84852-15-3	nonylphenols	4.8 ppm
140-31-8	2-piperazin-1-ylethylamine	71 mg/m ³
13463-67-7	titanium dioxide	330 mg/m ³
112945-52-5	Amorphous, fumed silica	100 mg/m ³

· **PAC-3:**

21645-51-2	aluminium oxide (hydrated) in wetted form (non-particulate)	440 mg/m ³
84852-15-3	nonylphenols	29 ppm
140-31-8	2-piperazin-1-ylethylamine	420 mg/m ³
13463-67-7	titanium dioxide	2,000 mg/m ³
112945-52-5	Amorphous, fumed silica	630 mg/m ³

7 Handling and storage

· **Handling:**· **Precautions for safe handling** Thorough dedusting· **Information about protection against explosions and fires:** No special measures required.· **Conditions for safe storage, including any incompatibilities**· **Storage:**· **Requirements to be met by storerooms and receptacles:** Store at temperatures not exceeding 10°C. Keep cool.· **Information about storage in one common storage facility:** Not required.· **Further information about storage conditions:** Keep receptacle tightly sealed.· **Specific end use(s)** No further relevant information available.

8 Exposure controls/personal protection

· **Additional information about design of technical systems:** No further data; see section 7.· **Control parameters**· **Components with limit values that require monitoring at the workplace:**

The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit.

At this time, the other constituents have no known exposure limits.

(Contd. on page 5)

-US

Safety Data Sheet

acc. to OSHA HCS

Printing date 09/04/2024

Revision 2

Reviewed on 09/04/2024

Trade name: **EB-155TC (PART B)**

(Contd. of page 4)

21645-51-2 aluminium oxide (hydrated) in wetted form (non-particulate)REL Long-term value: 2 mg/m³
as Al**13463-67-7 titanium dioxide**PEL Long-term value: 15* mg/m³
*total dust

REL See Pocket Guide App. A

TLV Long-term value: 0.2* 2.5** mg/m³
resp. fraction, *nanoscale, **finescale, A3**112945-52-5 Amorphous, fumed silica**TWA Short-term value: 0.8 mg/m³· **Additional information:** The lists that were valid during the creation were used as basis.· **Exposure controls**· **Personal protective equipment:**· **General protective and hygienic measures:**

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

Avoid contact with the eyes and skin.

· **Breathing equipment:** Not required.· **Protection of hands:**

Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

· **Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· **Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· **Eye protection:**

Tightly sealed goggles

*

9 Physical and chemical properties· **Information on basic physical and chemical properties**· **General Information**· **Appearance:****Form:** Liquid**Color:** Beige· **Odor:** Amine-like· **Odor threshold:** Not determined.

(Contd. on page 6)

US

Safety Data Sheet

acc. to OSHA HCS

Printing date 09/04/2024

Revision 2

Reviewed on 09/04/2024

Trade name: *EB-155TC (PART B)*

(Contd. of page 5)

· pH-value:	Not applicable.
· Change in condition	
Melting point/Melting range:	Undetermined.
Boiling point/Boiling range:	220.4 °C (428.7 °F)
· Flash point:	>115 °C (>239 °F)
· Flammability (solid, gaseous):	Not determined.
· Decomposition temperature:	Not determined.
· Ignition temperature:	Product is not selfigniting.
· Danger of explosion:	Product does not present an explosion hazard.
· Explosion limits:	
Lower:	2.1 Vol %
Upper:	10.5 Vol %
· Vapor pressure at 20 °C (68 °F):	0.1 hPa
· Density at 20 °C (68 °F):	1.45 g/cm ³ (12.10025 lbs/gal)
· Relative density	Not determined.
· Vapor density	Not applicable.
· Evaporation rate	Not applicable.
· Solubility in / Miscibility with Water:	Soluble.
· Partition coefficient (n-octanol/water):	Not determined.
· Viscosity:	
Dynamic:	Not applicable.
Kinematic:	Not applicable.
· Solvent content:	
VOC content:	0.00 %
Solids content:	100.0 %
· Other information	No further relevant information available.

10 Stability and reactivity

- **Reactivity** No further relevant information available.
- **Chemical stability**
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **Possibility of hazardous reactions** No dangerous reactions known.
- **Conditions to avoid** No further relevant information available.
- **Incompatible materials:** No further relevant information available.
- **Hazardous decomposition products:** No dangerous decomposition products known.

US

(Contd. on page 7)

Safety Data Sheet

acc. to OSHA HCS

Printing date 09/04/2024

Revision 2

Reviewed on 09/04/2024

Trade name: **EB-155TC (PART B)**

(Contd. of page 6)

11 Toxicological information

· Information on toxicological effects

· Acute toxicity:

· LD/LC50 values that are relevant for classification:

140-31-8 2-piperazin-1-ylethylamine

Oral LD50 2,140 mg/kg (rat)

Dermal LD50 880 mg/kg (rabbit)

· Primary irritant effect:

· **on the skin:** Caustic effect on skin and mucous membranes.

· **on the eye:** Strong caustic effect.

· **Sensitization:** Sensitization possible through skin contact.

· Additional toxicological information:

The product shows the following dangers according to internally approved calculation methods for preparations:

Harmful

Corrosive

Irritant

Swallowing will lead to a strong caustic effect on mouth and throat and to the danger of perforation of esophagus and stomach.

· Carcinogenic categories

· IARC (International Agency for Research on Cancer)

13463-67-7 titanium dioxide

2B

· NTP (National Toxicology Program)

None of the ingredients is listed.

· OSHA-Ca (Occupational Safety & Health Administration)

None of the ingredients is listed.

12 Ecological information

· Toxicity

· **Aquatic toxicity:** No further relevant information available.

· **Persistence and degradability** No further relevant information available.

· Behavior in environmental systems:

· **Bioaccumulative potential** No further relevant information available.

· **Mobility in soil** No further relevant information available.

· Ecotoxical effects:

· **Remark:** Very toxic for fish

· Additional ecological information:

· General notes:

Water hazard class 3 (Self-assessment): extremely hazardous for water

Do not allow product to reach ground water, water course or sewage system, even in small quantities.

Must not reach bodies of water or drainage ditch undiluted or unneutralized.

Danger to drinking water if even extremely small quantities leak into the ground.

Also poisonous for fish and plankton in water bodies.

Very toxic for aquatic organisms

· Results of PBT and vPvB assessment

· **PBT:** Not applicable.

· **vPvB:** Not applicable.

(Contd. on page 8)

US

Safety Data Sheet

acc. to OSHA HCS

Printing date 09/04/2024

Revision 2

Reviewed on 09/04/2024

Trade name: **EB-155TC (PART B)**

(Contd. of page 7)

· **Other adverse effects** No further relevant information available.

13 Disposal considerations

- **Waste treatment methods**
- **Recommendation:**
Must not be disposed of together with household garbage. Do not allow product to reach sewage system.
- **Uncleaned packagings:**
- **Recommendation:** Disposal must be made according to official regulations.
- **Recommended cleansing agent:** Water, if necessary with cleansing agents.

14 Transport information

· UN-Number	UN1759
· DOT, IMDG, IATA	
· UN proper shipping name	Corrosive solids, n.o.s. (nonylphenols, N-Aminoethylpiperazine)
· DOT	CORROSIVE SOLID, N.O.S. (nonylphenols, N-AMINOETHYLPIPERAZINE)
· IMDG, IATA	
· Transport hazard class(es)	
· DOT	
	
· Class	8 Corrosive substances
· Label	8
· IMDG	
 	
· Class	8 Corrosive substances
· Label	8
· IATA	
	
· Class	8 Corrosive substances
· Label	8
· Packing group	
· DOT, IMDG, IATA	III
· Environmental hazards:	Product contains environmentally hazardous substances: nonylphenols
· Marine pollutant:	Symbol (fish and tree)

(Contd. on page 9)

-US-

Safety Data Sheet

acc. to OSHA HCS

Printing date 09/04/2024

Revision 2

Reviewed on 09/04/2024

Trade name: **EB-155TC (PART B)**

(Contd. of page 8)

· Special precautions for user	Warning: Corrosive substances
· Hazard identification number (Kemler code): 80	
· EMS Number:	F-A,S-B
· Stowage Category	A
· Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code	Not applicable.
· Transport/Additional information:	
· DOT	
· Quantity limitations	On passenger aircraft/rail: 25 kg On cargo aircraft only: 100 kg
· IMDG	
· Limited quantities (LQ)	5 kg
· Excepted quantities (EQ)	Code: E1 Maximum net quantity per inner packaging: 30 g Maximum net quantity per outer packaging: 1000 g
· UN "Model Regulation":	UN 1759 CORROSIVE SOLID, N.O.S. (NONYLPHENOLS, N-AMINOETHYLPIPERAZINE), 8, III, ENVIRONMENTALLY HAZARDOUS

15 Regulatory information

- **Safety, health and environmental regulations/legislation specific for the substance or mixture**
No further relevant information available.
- **Sara**

· **Section 355 (extremely hazardous substances):**

None of the ingredients is listed.

· **Section 313 (Specific toxic chemical listings):**

84852-15-3 nonylphenols

· **TSCA (Toxic Substances Control Act):**

21645-51-2	aluminium oxide (hydrated) in wetted form (non-particulate)	ACTIVE
84852-15-3	nonylphenols	ACTIVE
140-31-8	2-piperazin-1-ylethylamine	ACTIVE
13463-67-7	titanium dioxide	ACTIVE

· **Hazardous Air Pollutants**

None of the ingredients is listed.

· **Proposition 65**

· **Chemicals known to cause cancer:**

13463-67-7 titanium dioxide

· **Chemicals known to cause reproductive toxicity for females:**

None of the ingredients is listed.

· **Chemicals known to cause reproductive toxicity for males:**

None of the ingredients is listed.

(Contd. on page 10)

-US-

Safety Data Sheet

acc. to OSHA HCS

Printing date 09/04/2024

Revision 2

Reviewed on 09/04/2024

Trade name: **EB-155TC (PART B)**

(Contd. of page 9)

· **Chemicals known to cause developmental toxicity:**

None of the ingredients is listed.

· **Carcinogenic categories**· **EPA (Environmental Protection Agency)**

None of the ingredients is listed.

· **TLV (Threshold Limit Value)**

13463-67-7 titanium dioxide

A4

· **NIOSH-Ca (National Institute for Occupational Safety and Health)**

13463-67-7 titanium dioxide

· **GHS label elements** The product is classified and labeled according to the Globally Harmonized System (GHS).· **Hazard pictograms**

GHS05 GHS07 GHS08

· **Signal word** Danger· **Hazard-determining components of labeling:**

nonylphenols
2-piperazin-1-ylethylamine
titanium dioxide

· **Hazard statements**

H302 Harmful if swallowed.
H314 Causes severe skin burns and eye damage.
H317 May cause an allergic skin reaction.
H351 Suspected of causing cancer. Route of exposure: Inhalation.
H361 Suspected of damaging fertility or the unborn child.

· **Precautionary statements**

P201 Obtain special instructions before use.
P202 Do not handle until all safety precautions have been read and understood.
P260 Do not breathe dusts or mists.
P264 Wash thoroughly after handling.
P270 Do not eat, drink or smoke when using this product.
P272 Contaminated work clothing must not be allowed out of the workplace.
P280 Wear protective gloves/protective clothing/eye protection/face protection.
P301+P312 If swallowed: Call a poison center/doctor if you feel unwell.
P301+P330+P331 If swallowed: Rinse mouth. Do NOT induce vomiting.
P303+P361+P353 If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P305+P351+P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P310 Immediately call a poison center/doctor.
P308+P313 IF exposed or concerned: Get medical advice/attention.
P321 Specific treatment (see on this label).
P333+P313 If skin irritation or rash occurs: Get medical advice/attention.
P363 Wash contaminated clothing before reuse.
P405 Store locked up.
P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

(Contd. on page 11)

Safety Data Sheet

acc. to OSHA HCS

Printing date 09/04/2024

Revision 2

Reviewed on 09/04/2024

Trade name: **EB-155TC (PART B)**

(Contd. of page 10)

· **Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· **Department issuing SDS:** Environment protection department.· **Contact:** EHS Personnel· **Date of preparation / last revision** 09/04/2024 / 1· **Abbreviations and acronyms:**

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA)

HMIS: Hazardous Materials Identification System (USA)

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

NIOSH: National Institute for Occupational Safety

OSHA: Occupational Safety & Health

TLV: Threshold Limit Value

PEL: Permissible Exposure Limit

REL: Recommended Exposure Limit

Acute Toxicity - Oral 4: Acute toxicity – Category 4

Skin Corrosion 1B: Skin corrosion/irritation – Category 1B

Eye Damage 1: Serious eye damage/eye irritation – Category 1

Sensitization - Skin 1: Skin sensitisation – Category 1

Carcinogenicity 2: Carcinogenicity – Category 2

Toxic to Reproduction 2: Reproductive toxicity – Category 2

· *** Data compared to the previous version altered.**

US